

TITAN-RR2<u>0-A</u>

TITAN-RR5

TITAN-RR18-LP

20 000 L AIRCRAFT REFUELLER



Ĺ	TITAN-RR38
ſ	TITAN-STR35-LP
1	TITAN-STR45-LP
1	TITAN-STR65
1	TITAN-HD150
1	TITAN-HD230
6	
L	TITAN-HD230-LP

Non contractual picture

AVIATION FUEL	JET A1
FLOW RATE	55 m3/h – 900 LPM
DIMENSIONS (LxWxH)	Approximately 10m x 2,5m x 3,3m
ERGONOMICS	In conformity with TITAN AERO ergonomics charter
CONFORMITY	JIG 1 issue 13 EN 12312-5 EN 1361-C El 1529 El 1581 6th édition EN 1915-1
USE	Exclusively for airport use
PAINTING	White RAL 9010 Polyurethane

CHASSIS

DESIGN	Rigid
AXLES LAYOUT	4 x 2
DRIVING	LHD or RHD
ADR HAZMAT	Compliant
SPEED GOVERNOR	Up to 25 km/h

PLATFORM

PLATFORM	Not applicable
COMPLIANCE	Not applicable
TANK	
USEFUL CAPACITY	20 000 L – 5 200 USG
MATERIAL	Aluminum
SHAPE	Biconical Single-compartment
LOADING	Bottom loading Fuelling side

DISTRIBUTION

UNDERWING LINE	1 underwing line - 55m3/h - 900 LPM on hydraulic reel
OVERWING LINE	1 overwing line - 12 m3/h - 200 LPM on hydraulic reel allowing a gravity-fed distribution
DECK UNDERWING LINE	Not applicable
FILTRATION	Stainless steel water separator filter (FWS)
METER	Meter with electronic readout
2 ND REGULATION	Not applicable
SAMPLING	Jar support after filtration
PIPES	304 L Stainless steel
ANTI-CORROSION PROTECTION	Hot zinc metallized structure Surfaces finishing according to TITAN AERO specs



OPTIONS \sim

OPERATION

RR20-001

RR20-002

RR20-003

RR20-004

RR20-005

RR20-006

RR20-007

RR20-008

RR20-009

RR20-010

RR20-011

RR20-012

RR20-013

Customer's logo stickers

Scully tank level sensor

Towing pin for towable ladder (3,5t max)

Ladder 3+1 with support (N/A with O12 & O13)

Ladder 4+1 with support (N/A with O11 & O13)

Ladder 5+1 with support (N/A with O11 & O12)

SAFETY	
RR20-S01	Set of 2 extinguisher boxes (N/A with SO2)
RR20-S02	Set of 2 extinguishers inclined/open scabbards (N/A S01)
RR20-S03	Set of 2+1 extinguishers
RR20-S05	Single handrail (pneumatical)
RR20-S06	Double handrail (pneumatical)
RR20-S07	Camera + Screen : mounted at the back (reverse)
RR20-S09	L&R sides protection guards
RR20-S10	Reflecting stripes
RR20-S11	Bonding reel on opposite side
RR20-S13	Access cab handles with colored safety code
RR20-S15	Wheel chock with its support

企COMFORT	
RR20-C02	Driver seat cover
RR20-C03	Mudflaps on front of mudguards (rear is already included)
RR20-C04	Strap for driver's door opening
RR20-C05	Additional lighting system (draining points)
RR20-C08	Hose spiral protection
RR20-C09	Support inside cab for payment terminal

© QUALITY	,
RR20-Q01	Weight & measures dipstick (T)
RR20-Q02	Regulation test
RR20-Q03	Sample jar kit with CWD tray, recovery tank & reinjection
RR20-Q04	Sample jar cover protection
RR20-Q05	SSAFCON tray
RR20-Q06	Electronic thermometer and densimeter
RR20-Q07	Isolation flanges mounted on tank suction and foam return lines
RR20-Q08	Ticket printer inside cab

OHOMOLOGATION	
RR20-H01	MID homologation
RR20-H02	Official tank calibration

* FREEZE	
RR20-F01	Cabinet with rolling doors
RR20-F02	Cabinet with swivelling doors on both sides



www.titan-aero.com

6

Defuelling External suction Large display Tank mechanical gauge Trailer kit 2"1/2 aviation coupling on bottom loading 4" industrial coupling on bottom loading

V02 – EN | www.titan-aero.com | 170 rue Clément Ader, Zone Industrielle Nord, 69400 Arnas, France | Fax +33 (0) 474 655 297 Siret : 980 585 277 00018 | Code NAF 2927Z